

edo GTS

Specifications

Engine	V8, front engine
Power	450 hp / (331 kW) at 6,850 rpm
Max. torque	530 Nm (391 ft-lb) at 3,800 rpm

Performance

Top speed	270 km/h (168 mph)
0 - 100 km/h (0 - 62 mph)	6.4 sec.

Features

- **Engine**
Power increase to 450 hp via:
New ECU calibration, optimized on the dyno
New high-flow catalytic converters
Performance air filter insert
- **Suspension**
Adjustable edo/KW sport suspension set.
Individually adjustable compression and rebound damping. Height-adjustable with TÜV-approved adjustment range. Continuously variable rebound damping, 14-way adjustable compression damping.
- **Brake system**
New front rotors and six-piston mono-block fixed calipers with thicker and larger diameter rotors, upsized brake pads.
Stock GTS: 350 x 34 mm (13.8 x 1.4 inches)
edo GTS: 380 x 38 mm (15.0 x 1.5 inches)
- **Wheel/tire combination**
New 22 inch forged wheels with stainless steel outer rims:
Front: 10x22 with 295/30 ZR22 Continental Cross Contact UHP
Rear: 11x22 with 295/30 ZR22 Continental Cross Contact UHP
Custom-painted wheels/wheel centers optional.
- **Aerodynamics**
 - Hood with power domes, painted
 - Lower front lip with 4 fog lights and wire mesh inserts, painted

As of Oct. 2008